

WELDPRO 360 LRW-10ML Mig Welding Arm



WELDPRO 360 LRW-10ML Mig Welding Arm



WELDPRO 360 LRW-10ML Mig Welding Arms reduce or eliminate non-arc time welding-related tasks, shop floor clutter, and employee safety issues. This arm provides complete coverage anywhere with-in a 40' diameter semi-circular welding zone. The welding arm's main pivot assembly mounts to your existing building column, freestanding column or the optional mobile base and column assembly.

The WELDPRO 360-LRW-10-ML is

made with two arms; a primary arm and a secondary arm. The primary arm is the short arm which is attached to the column-mounted pivot assembly. The pivot assembly has a maximum of 192° of semi-circular rotation. It provides complete coverage within a 40' diameter semi-circle when using a 15' Mig welding gun.

Unique to this design is the articulating joint arrangement that connects the primary and secondary arms allowing the secondary arm to be manually raised and lowered 7'-8". The maximum vertical reach is 21'-6" with a standard mounting height of 8'. Arm rotation for the primary arm and the raising and lowering of the secondary arm is done manually.



www.weldpro360.com

The wire feeder is mounted on the end of the secondary arm. We recommend



wire feeders that are capable of controlling the power supply remotely. This eliminates wasted time walking back and forth to the welder to change weld settings. Welding wire conduit liner, power cable and gas hoses are all contained within the tubular arms eliminating safety hazards and shop floor clutter. This makes for a neat, clean organized shop.

Standard Features

- 192° of bi-directional rotation
- Boom Reach Anywhere within a 20' diameter semi-circle
- Welding Reach Anywhere with a 40' diameter semi-circle with 15' Mig gun
- Secondary Arm raises and lowers 7'-8"
- C Maximum vertical reach 21'-6" with 15' Mig Gun
- Rotation of the Primary Arm and raising and
- lowering the Secondary Arm is done manually Powder Coated Finish


Options



WELDPRO 360 LRW Hi Vacuum Fume Extraction systems are integrated with the welding arm. Available in boom mount or mobile.



□ Fume Extraction Guns – Air or Water Cooled



- Welding Wire Enclosures up to 60 Lb spools

 keeps dust and dirt out of wire, eliminiating
 wire feeding problems and excessive liner wear.
- Floor Mounted Columns available in 8' or 10' height clearance under Welding Arm



MOBILE BASE available with 8' column

 includes: Skid to mount welding equipment, and
 gas cylinder mount

Productivity Advantages

- Reduced time spent on non-welding tasks More time welding
- Clean, organized welding cell
- Eliminates tripping hazards and shop floor clutter
 Increased operator safety, motivation, and productivity



17079 Muskrat Ave., Adelanto, CA 92301 U.S.A. Ph. 760.246.8766 Fax 760.246.8702